



10' 8'6" dv DNV 2.7-1/EN12079 offshore container

Advantages

Equipped with checker plate steel floor / 5 hinges each rear door / offshore pad-eyes within ISO / low tare – high payload

CSC / TIR / DNV 2.7-1 EN12079 / NORSOK M501-A1

Optional supplied with DNV 2.7-1 certified wire rope superlooped sling (rigging)

Upper and lower lashing points on three sides.

- From stock available for sales and rental
- Modification work possible under Lloyds certification
- Some of our other designs are: 6' mini / 10' half height / 20' half height heavy duty / 20' 8'6" dnv / 20' 8'6" low roof / 20' 8'6" open top / 20' 9'6" high

Classification		Dimension	
External	Length	2.991 $\begin{smallmatrix} +0 \\ -6\text{mm} \end{smallmatrix}$	9' 9 ³ / ₄ " $\begin{smallmatrix} +0 \\ -1/4" \end{smallmatrix}$
	Width	2.438 $\begin{smallmatrix} +0 \\ -5\text{mm} \end{smallmatrix}$	8' 0" $\begin{smallmatrix} +0 \\ -3/16" \end{smallmatrix}$
	Height	2.591 $\begin{smallmatrix} +0 \\ -5\text{mm} \end{smallmatrix}$	8' 6" $\begin{smallmatrix} +0 \\ -3/16" \end{smallmatrix}$
Internal	Length	2.829 mm	9' 3 ³ / ₈ "
	Width	2.346 mm	7' 8 ³ / ₈ "
	Height	2.352,5 mm	7' 8 ⁵ / ₈ "
Door opening	Width	2.338 mm	7' 8 ³ / ₆₄ "
	Height	2.251 mm	7' 4 ⁵ / ₈ "
Internal cubic capacity		15,6 CU.m	551 CU.ft
Max. gross weight		11.500 kg	25.350 lb
Tare weight		2.000 kg	4.410 lb
Maximum payload		9.500 kg	20.940 lb
Stacking test load (per post)		22.860 kg	50.400 lb